

Safety Data Sheet  
AWLFAIR LW STANDARD CONVERTER



Bulk Sales Reference No.:  
SDS Revision Date:  
SDS Revision Number:

Sales  
Order: {SalesOrd}  
OD7200  
03/03/2017  
E3-3

1. Identification of the preparation and company

1.1. Product identifier

Product Identity AWLFAIR LW STANDARD CONVERTER  
Bulk Sales Reference No. OD7200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.  
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Akzo Nobel Coatings  
International Paint LLC  
6001 Antoine Drive  
Houston, Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300  
International Paint (713) 527-3887  
Poison Control Center (800) 854-6813  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Skin Corr. 1B;H314 Causes severe skin burns and eye damage.  
Eye Dam. 1;H318 Causes serious eye damage.  
Skin Sens. 1;H317 May cause an allergic skin reaction.  
Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

P260 Do not breathe mist / vapors / spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P333+313 If skin irritation or a rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating            Health: 2            Flammability: 1            Reactivity: 0

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Limestone CAS Number: 0001317-65-3	10 - 25	----	[1]
Cycloaliphatic amine CAS Number: TS-KH3025	10 - 25	----	[1]
Glass, oxide, chemicals CAS Number: 0065997-17-3	10 - 25	----	[1]
Benzyl alcohol CAS Number: 0000100-51-6	1.0 - 10	Acute Tox. 4;H332 Acute Tox. 4;H302	[1]
m-Xylene-alpha, alpha'-diamine CAS Number: 0001477-55-0	1.0 - 10	Acute Tox. 4;H302 Acute Tox. 3;H331 Skin Corr. 1;H314 Skin Sens. 1;H317 Aquatic Chronic 3;H412	[1][2]
Tetraethylenepentamine CAS Number: 0000112-57-2	1.0 - 10	Acute Tox. 4;H312 Acute Tox. 4;H302 Skin Corr. 1B;H314 Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]
Iron oxide CAS Number: 0001309-37-1	1.0 - 10	----	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.

## OD7200\_E3

Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
4.2. Most important symptoms and effects, both acute and delayed	
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

#### 5.2. Special hazards arising from the substance or mixture

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

#### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No.

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

#### 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

### 7. Handling and storage

#### 7.1. Precautions for safe handling

##### Handling

Vapors may cause flash fire or ignite explosively.

##### In Storage

Keep away from heat, sparks and flame.

#### 7.2. Conditions for safe storage, including any incompatibilities

## OD7200\_E3

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection
--

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0000100-51-6	Benzyl alcohol	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0000112-57-2	Tetraethylenepentamine	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0001309-37-1	Iron oxide	OSHA	10 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust, listed under Rouge); 5 mg/m3 TWA (respirable fra
		ACGIH	5 mg/m3 TWA (respirable fraction)
		NIOSH	5 mg/m3 TWA (dust and fume, as Fe)2500 mg/m3 IDLH (dust and fume, as Fe)
		Supplier	
		OHSA, CAN	5 mg/m3 TWA (respirable)
		Mexico	5 mg/m3 TWA LMPE-PPT10 mg/m3 STEL [LMPE-CT] (as Fe)
		Brazil	
0001317-65-3	Limestone	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	
		OHSA, CAN	
		Mexico	10 mg/m3 TWA LMPE-PPT20 mg/m3 STEL [LMPE-CT]
		Brazil	
0001477-55-0	m-Xylene-alpha, alpha'-diamine	OSHA	0.1 mg/m3 Ceiling
		ACGIH	0.1 mg/m3 Ceiling
		NIOSH	0.1 mg/m3 Ceiling
		Supplier	

OD7200\_E3

		OHSA, CAN	0.1 mg/m3 Ceiling
		Mexico	
		Brazil	
0065997-17-3	Glass, oxide, chemicals	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
TS-KH3025	Cycloaliphatic amine	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	

Health Data

CAS No.	Ingredient	Source	Value
0000100-51-6	Benzyl alcohol	NIOSH	
0000112-57-2	Tetraethylenepentamine	NIOSH	
0001309-37-1	Iron oxide	NIOSH	Benign pneumoconiosis termed siderosis
0001317-65-3	Limestone	NIOSH	Eye and skin irritation Physical irritation
0001477-55-0	m-Xylene-alpha, alpha'-diamine	NIOSH	Skin irritation systemic effects
0065997-17-3	Glass, oxide, chemicals	NIOSH	
TS-KH3025	Cycloaliphatic amine	NIOSH	

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000100-51-6	Benzyl alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000112-57-2	Tetraethylenepentamine	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001309-37-1	Iron oxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001317-65-3	Limestone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001477-55-0	m-Xylene-alpha, alpha'-diamine	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0065997-17-3	Glass, oxide, chemicals	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
TS-KH3025	Cycloaliphatic amine	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

## OD7200\_E3

		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
--	--	------	--

### 8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties
-------------------------------------

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	35 (°C) 95 (°F)
Flash Point	100 (°C) 212 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	0.70
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.

10. Stability and reactivity
------------------------------

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

## OD7200\_E3

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

### 10.3. Possibility of hazardous reactions

No data available

### 10.4. Conditions to avoid

No data available

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information
-------------------------------

#### Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Limestone - (1317-65-3)	No data available	No data available	No data available	No data available
Cycloaliphatic amine - (TS-KH3025)	No data available	No data available	No data available	No data available
Glass, oxide, chemicals - (65997-17-3)	No data available	No data available	No data available	No data available
Benzyl alcohol - (100-51-6)	1,230.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	No data available	4.178, Rat - Category: 4
m-Xylene-alpha, alpha'-diamine - (1477-55-0)	930.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	2.40, Rat - Category: 3	No data available
Tetraethylenepentamine - (112-57-2)	2,140.00, Rat - Category: 5	No data available	No data available	No data available
Iron oxide - (1309-37-1)	10,000.00, Rat - Category: NA	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information
----------------------------

OD7200\_E3

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Limestone - (1317-65-3)	Not Available	Not Available	Not Available
Cycloaliphatic amine - (TS-KH3025)	Not Available	Not Available	0.00 ( hr),
Glass, oxide, chemicals - (65997-17-3)	Not Available	Not Available	Not Available
Benzyl alcohol - (100-51-6)	10.00, Lepomis macrochirus	55.00, Daphnia magna	700.00 (72 hr), Algae
m-Xylene-alpha, alpha'-diamine - (1477-55-0)	100.00, Oncorhynchus mykiss	16.00, Daphnia magna	Not Available
Tetraethylenepentamine - (112-57-2)	420.00, Poecilia reticulata	24.00, Daphnia magna	2.00 (72 hr), Pseudokirchneriella subcapitata
Iron oxide - (1309-37-1)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number

UN1759

14.2. UN proper shipping name

CORROSIVE SOLID, N.O.S. (FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENATED, 3, 6, 9-TRIAZAUNDECAMETHYLENEDIAMINE)

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

DOT Proper Shipping Name CORROSIVE SOLID, N.O.S. (FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENATED, 3, 6, 9-TRIAZAUNDECAMETHYLENEDIAMINE)

DOT Hazard Class Corrosive,8

IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name CORROSIVE SOLID, N.O.S. (FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENATED, 3, 6, 9-TRIAZAUNDECAMETHYLENEDIAMINE)

IMDG Hazard Class Sub Class Corrosive,8 Not applicable



UN / NA UN1759

Number

DOT Packing III

Group

IMDG III

Packing

Group

CERCLA/DOT Not Applicable gal. / Not Applicable lbs.

RQ

System 248

Reference

Code

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information
----------------------------

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification D2B E

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):  
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :  
(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%) :  
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :  
(No Product Ingredients Listed)

Mass RTK Substances (>1%) :

Benzyl alcohol

Iron oxide

Limestone

m-Xylene-alpha, alpha'-diamine

Tetraethylenepentamine

Penn RTK Substances (>1%) :

Benzyl alcohol

Iron oxide

Limestone

m-Xylene-alpha, alpha'-diamine

Tetraethylenepentamine

Penn Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)

RCRA Status:  
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

Iron oxide

Limestone

m-Xylene-alpha, alpha'-diamine

Tetraethylenepentamine

N.J. Special Hazardous Substances (>.01%) :

Quartz

Tetraethylenepentamine

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :  
(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0%):  
Quartz

Proposition 65 - Female Repro Toxins (>0%):  
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):  
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):  
(No Product Ingredients Listed)

16. Other information
-----------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

SECTION 2: Hazards identification

SECTION 9: Physical and chemical properties

SECTION 11: Toxicological information

End of Document