POLISH # 2

This WARNING is our compliance with the requirements set forth in California's "Safe Drinking Water and Toxic Enforcement Act" of 1986.
Otherwise known as Proposition 65.

WARNING:

THIS PRODUCT CONTAINS A CHEMICAL (S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM. THE AMOUNT OF THE CHEMICAL (S) IN THIS PRODUCT IS VERY SMALL AND WE BELIEVE THAT IT DOES NOT POSE A SIGNIFICANT RISK IN NORMAL USE OF THIS PRODUCT.

++

Prepared According to the Osha Hazard Communication Standard (29 CFR 1910.1200)

Danger! HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE EYE IRRITATION COMBUSTABLE. KEEP OUT OF REACH OF CHILDREN.

SAFETY DATA SHEETS

EMERGENCY PHONE: FIBERGLASS SERVICES, INC. 310-327-0080 OR 310-327-0090

SDS REFERENCE: POLISH #2

SECTION I - IDENTIFICATION

PRODUCT: POLISH #2

SYNONYMS: CLEANER #2

CHEMICAL: N/A

CAS NO: UNKNOWN

SECTION II - HAZARDOUS INGREDIENTS

COMPOSITION:

CONTAINS HYDROCARBON DISTILLATE (CAS 64742-47-8) 2%
ISOPROPANOL <9 CAS 67630) 1%

SECTION III - HEALTH INFORMATION

INHALATION:

BREATHING THE VAPOR AT CONCENTRATIONS IN AIR THAT EXCEED THE RECOMMENDED EXPOSURE STANDARD CAN CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. SEE ADDITIONAL HEALTH DATA.

INGESTION:

NOT EXPECTED TO HAVE ACUTE SYSTEMIC TOXICITY BY INGESTION. NOTE TO PHYSICIAN: INGESTION OF THIS PRODUCT OR SUBSEQUENT VOMITING CAN RESULT IN ASPIRATION OF LIGHT HYDROCARBON LIQUID WHICH CAN CAUSE PNEUMONITIS.

EYE CONTACT:

EXPECTED TO CAUSE NO MORE THAN MINOR EYE IRRITATION.

SKIN CONTACT:

EXPOSED EMPLOYEES SHOULD EXERCISE REASONABLE PERSONAL CLEANLINESS; THIS INCLUDES CLEANSING EXPOSED SKIN AREAS SEVERAL TIMES DAILY WITH SOAP AND WATER, AND LAUNDERING OR DRY CLEANING SOILED WORK CLOTHING AT LEAST WEEKLY.
GLOVES RESISTANT TO CHEMICALS AND PETROLEUM DISTILLATES RECOMMENDED.

CARCENOGENICITY:

NONE KNOWN

SECTION IV - OCCUPATIONAL EXPOSURE LIMITS

PEL: NOT ESTABLISHED

TLV: NOT ESTABLISHED

NO FEDERAL OSHA EXPOSURE STANDARD OR ACCITH TLV HAS BEEN ESTABLISHED FOR THIS MATERIAL. BASED ON INFORMATION REVIEWED TO DATE, WE RECOMMEND AN EXPOSURE STANDARD OF 250 PPM FOR A DAILY 8-HOUR EXPOSURE.

SECTION V - EMERGENCY FIRST AID PRODEDURE

SWALLOWING:

IF SWALLOWED, GIVE WATER OR MILK TO DRINK AND TELEPHONE FOR MEDICAL ADVICE. DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. IF MEDICAL ADVICE CANNOT BE OBTAINED, THEN TAKE THE PERSON AND PRODUCT CONTAINER TO THE NEAREST MEDICAL EMERGENCY TREATMENT CENTER OR HOSPITAL.

SKIN CONTACT:

WASH SKIN THROUGHLY WITH SOAP AND WATER. LAUNDER CONTAMINATED CLOTHING. SEE DOCTOR IF IRRITATION OCCURES.

EYE CONTACT:

FLUSH EYES IMMEDIATELY WITH FRESH WATER FOR AT LEAST 15 MINUTES WHILE HOLDING THE EYELIDS OPEN. IF IRRITATION PERSISTS, SEE A DOCTOR.

INHALATION:

IF THERE ARE SIGNS OR SYMPTOMS AS DESCRIBED IN THIS BULLETIN DUE TO BREATHING THE MATERIAL, MOVE THE PERSON TO FRESH AIR. IF BREATHING HAS STOPPED, APPLY ARTIFICIAL RESPIRATION. CALL A DOCTOR.

SECTION VI - PHYSICAL DATA

BOILING POINT:	NOT DETERMINED
MELTING POINT:	NOT APPLICABLE
VAPOR PRESSURE:	1MM HG @ 77 DEGREES F
SPECIFIC GRAVITY:	1.10
VAPOR DENSITY:	N/A

SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND COLOR: WHITE SEMI-PASTE

SECTION V11 - FIRE AND EXPLOSION HZARDS

FLASH POINT AND METHOD USED: ABOVE 250 DEGREES F
AUTO-ICNITION TEMPERATURE: NOT ESTABLISHED
FLAMMABLE LIMITS IN AIR, & BY VOL. LOWER: NOT ESTABLISHED
FLAMMABLE LIMITS IN AIR, & BY VOL. UPPER: NOT ESTABLISHED
NFPA RATING: NO NFPA RATING

SPECIAL FIRE FIGHTING PRODEDURE & PRECAUTIONS:

EXTINGUISHING MEDIA: CO2, DRY CHEMICAL, FOAM, and WATER & FOG.

FOR FIRES INVOLVING THIS MATERIAL DO NOT ENTER ANY ENCLOSED OR CONFINED FIRE SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT. THIS MAY INCLUDE SELF-CONTAINED BREATHING APPARATUS TO PROTECT AGAINST THE HAZARDOUS EFFECTS OF NORMAL PRODUCTS OF COMBUSTION OR OXYGEN DEFICIENCY. READ THE ENTIRE M.S.D.S. (MATERIAL SAFETY DATA SHEET)

UNUSAL FIRE & EXPLOSION HAZARDS

(SECTION X11)

SECTION V111 - REACTIVITY

STABILITY:

(THERMAL, LIGHT, ETC.) : STABLE

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

CONDITION & MATERIALS TO AVOID:

MAY REACT WITH STRONG OXIDIZING MATERIALS.

HAZARDOUS DECOMPOSITION PRODUCTS:

NORMAL COMBUSTION FORMS CARBON DIOXIDE AND WATER VAPOR: INCOMPLEE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

SECTION IX – EMPLOYEE PROTECTION

CONTROL MEASURES:

HANDLE IN THE PRESENCE OF ADEQUATE VENTILATION.

RESPIRATORY PROCTECTION:

WHERE EXPOSURE IS LIKELY TO EXCEED ACCEPTABLE CRITERIA (SEE SECTIONS 11 AND IV) USE NIOSH/OSHA APPROVED RESPIRATORY EQUIPMENT. RESPIRATIONS SHOULD BE SELECTED BASED ON THE FORM AND CONCENTRATION OF CONTAMINANT IN AIR AND IN ACCORDANCE WITH OSHA. (29 CFR 1910.134)

PROTECTIVE CLOTHING:

WEAR GLOVES AND PROTECTIVE CLOTHING WHICH ARE IMPERVIOUS TO THE PRODUCT FOR THE DURATION OF ANTICIPATED EXPOSURE IF THERE IS POTENTIAL FOR SKIN CONTACT.

EYE PROTECTION:

WEAR SAFETY GLASSES MEETING THE SPECIFICATIONS OF ANSI STANDARD Z87.1 WHERE NO CONTACT WITH THE EYE IS ANTICIPATED. CHEMICAL SAFETY GOGGLES MEETING THE SPECIFICATIONS OF ANSI STANDARD Z87.1 SHOULD BE WORN WHENEVER THERE IS THE POSSIBILITY OF SPLASHING OR OTHER CONTACT WITH THE EYES.

SECTION X – ENVIROMENTAL PROTECTION

ENVIROMENTAL PRECAUTIONS:

CERTAIN GEOGRAPHICAL AREAS HAVE AIR POLLUTION REGULATIONS SHOULD BE STUDIED TO DETERMINE IF THIS MATERIAL IS REGULATED IN THE AREA WHERE IT IS TO BE USED.

SPILL OR LEAK PECAUTIONS:

ELIMINATE ALL OPEN FLAME IN VICINITY OF SPILL OR RELEASE VAPOR. STOP THE SOURCE OF THE LEAK OR RELEASE. CLEAN UP RELEASES AS SOON AS POSSIBLE, OBSERVING PRECAUTIONS IN SPECIAL PROTECTIVE INFORMATION CONTAIN LIQUID TO PREVENT FURTHER CONTAMINATION OF SOIL, SURFACE WATER OR GROUNDWATER, CLEAN UP SMALL SPILLS USING APPROPRIATE TECHNIQUES SUCH AS SORBENT MATERIALS OR PUMPING. WHERE FEASIBLE AND APPROPRIATE, REMOVE CONTAMINATED SOIL. FOLLOW PRESCRIBED PROCEDURES FOR REPORTING AND RESPONDING TO LARGER RELEASES.

WASTE DISPOSAL:

PLACE CONTAMINATED MATERIALS IN DISPOSABLE CONTAINERS AND DISPOSE OF IN A MANNER CONSISTENT WITH APPLICABLE REGULATIONS. CONTACT LOCAL ENVIRONMENTAL OR HEALTH AUTHORITIES FOR APPROVED DISPOSAL OF THIS MATERIAL.

SECTION X1 – REGULATORY CONTROLS

DEPARTMENT OF TRANSPORATION:

DOT CLASSIFICATION: COMPOUND CLEANING NOT A
DOT PROPER SHIPPING NAME: #2 CLEANER

OTHER REGULATORY REQUIREMENTS:

NONE

SECTION X11 – PRECAUTIONS: HANDLING, STORAGE AND USAGE

++

++

ADDITIONAL HEALTH DATA

SIGNS AND SYMPTOMS OF CENTRAL NERVOUS SYSTEM EFFECTS MAY INCLUDE ONE OR MORE OF THE FOLLOWING: HEADACHE, DIZZINESS, LOSS OF APPETITE, WEAKNESS AND LOSS OF COORDINATION. AFFECTED PERSONS USUALLY EXPERIENCE COMPLETE RECOVERY WHEN REMOVED FROM THE EXPOSURE AREA.

SPECIAL PRECAUTIONS

READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL.

DO NOT USE OR STORE NEAR FLAME, APARKS OR HOT SURFACES. USE ONLY IN WELL VENTILATED AREA. KEEP CONTAINER CLOSED.

DO NOT WELD, HEAT OR DRILL CONTAINER. REPLACE CAP OR BUNG. EMPTIED CONTAINER STILL CONTAINS HAZRDOUS OR EXPLOSIVE VAPOR OR LIQUID.

CAUTION: DO NOT USE PRESSURE TO EMPTY DRUM OR EXPLOSION MAY RESULT.

REACTIVITY: 1. FLAMMABILITY: 2. HEALTH: 1* (*INDICATES MAY HAVE CHRONIC TOXICITY)

++

THE ABOVE INFORMATION IS BASED ON DATA OF WHICH WE ARE AWARE AND IS BELIEVED TO BE CORRECT AS OF THE DATE HEREOF. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS EYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR AND SINCE DATA MADE AVAILABLE SUBSEQUENT TO THE DATE HEREOF MAY SUGGEST MODIFICATIONS OF THE INFORMATION. WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF ITS USE. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE.

PREPARED BY: FIBERGLASS SERVICES, INC. DBA: SURF SUPPLY