



Safety Data Sheet

Section 1: Identification of the Product/Company

Product Identifier:

Product Name: CLEAR WEBBING SOLUTION

Product Code: 800

Relevant identified uses of the substance or mixture

Recommended use:

As a gel coat additive to obtain spatter or cobweb

Uses advised against:

None identified

Details of the supplier of the safety data sheet

Manufacturer:

Kel-Glo Corporation
54 N.E. 73rd Street
Miami, FL 33138
United States
www.kel-glo.com

Telephone (General)

(305) 751-5641

Emergency telephone number

Manufacturer:

(800) 424-9300 (Chemtrec) USA
+ 1 (703) 527-3887 (Chemtrec) International

Section 2: Hazards Identification

Classification of the substance or mixture

GHS-US classification

Flammable liquids:	Category 2, H226
Flammable liquids:	Category 3, H225
Acute toxicity, Oral:	Category 5, H303
Acute toxicity, Inhalation: Dust and Mist	Category 2, H330
Acute toxicity, Inhalation: Vapors	Category 4, H332
Acute toxicity, Inhalation: Gas	Category 1, H330



Safety Data Sheet


Skin irritation:	Category 2, H315
Eye irritation:	Category 2, H319
Skin sensitization:	Category 1, H317
Germ cell mutagenicity:	Category 2, H341
Carcinogenicity:	Category 2, H351
Reproductive toxicity:	Category 2, H361
Specific target organ systemic toxicity (single exposure):	Category 3, H335
Specific target organ systemic toxicity (single exposure):	Category 3, H336
Specific target organ systemic toxicity (repeated exposure):	Category 2, H371
Specific target organ systemic toxicity (repeated exposure):	Category 1, H372
Aspiration hazard:	Category 2, H305
Hazardous to aquatic environment: Chronic	Category 2, H411
Hazardous to aquatic environment: Acute	Category 2, H401

Label elements

GHS-US labeling

The substance is classified and labeled according to the Globally Harmonized System (GHS).

Hazard Pictograms (GHS-US)



Signal words (GHS-US):

Danger

Hazards statements (GHS-US):

H225 Highly flammable liquid and vapor
H315 Causes skin irritation

H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H336 May cause drowsiness and dizziness
H401 Toxic to aquatic life
H411 Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US)



Safety Data Sheet

Prevention:

P210 Keep away from heat, hot surfaces, open flames, sparks. – No Smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion proof electrical, lighting and ventilating equipment
P242 Use non-sparking tools
P243 Take precautionary measures against static discharge
P261 Avoid breathing mist, spray, vapors
P264 Wash hands thoroughly after handling
P271 Use only outdoors or in a well ventilated area
P273 Avoid release to the environment
P280 Wear protective gloves, clothing, and eye/face protection

Response:

P301+P312 IF SWALLOWED: Call POISON CENTER and or doctor if you feel unwell
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: remove victim to fresh air and keep at rest in position comfortable for breathing
P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
P337 + P313 If eye irritation persists: Get medical advice/attention
P370 + P378 In case of fire: Use dry chemical powder, alcohol resistant foam, Carbon Dioxide for extinction

Storage:

P403+P233 store in a well ventilated place. Keep container tightly closed



Safety Data Sheet

P403 + P235 Store in a well ventilated place. Keep cool

P405 Store locked up

Disposal:

P501 Dispose of contents and containers in accordance with local, regional and international regulations

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)-Annex III

Other hazards

No other information available

Unknown acute toxicity (GHS-US)

No data available

Section 3: Composition/information on ingredients

Substances

Name	Product Identifier	% by weight	GHS-US classification
Toluene	CAS # 108-88-3	30-50	Flammable liquid 2, H225 Skin irritant 2, H315 Reproductive 2, H361 STOT SE 3, H336 STOT RE 2, H373 Aspiration toxicity 1, H304
Acetone	CAS # 67-64-1	30-50	Flammable liquid 2, H225 Acute toxicity 3, H331 Eye irritant 2A, H319 STOT SE 3, H335
Methyl Ethyl Ketone	CAS # 78-93-3	1-5	Flammable liquid 2, H225 Eye irritation 2, H319 STOT SE 3, H336
Isopropanol	CAS # 67-63-0	<1	Flammable liquid 2, H225



Safety Data Sheet

			Eye irritation 2A, H319 STOT SE 3, H336
Nitrocellulose	CAS # 9004-70-0	2-10	Explosive 1.1, H201

Amounts specified are typical and do not represent a specification. Any other ingredients are either proprietary, non-hazardous or present in amounts below the reportable limits.

Section 4: First aid measures

Description of necessary first aid measures

First-aid measures general:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

First-aid measures after inhalation:

If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.

First-aid measures after skin contact:

Immediately remove contaminated clothing and shoes. Wash the affected area with plenty soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. Seek medical attention if symptoms occur.

First-aid measures after eye contact:

Immediately flush eyes with copious amount of clean water for an extended time (not less than 15 minutes). Flush longer if there is any indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. Seek medical attention if irritation develops or persists.

First-aid measures after ingestion:

Do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth to an unconscious or convulsing person. Rinse out the mouth with water. Get medical attention immediately.

Most important and effects, both acute and delayed

Symptoms:

Irritation may occur. Pre-existing skin problems may be aggravated by prolonged or repeated contact.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically



Safety Data Sheet

Section 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use water fog, foam, dry chemical or Carbon Dioxide

Unsuitable extinguishing media:

High volume water jet

Special hazards arising from the substance or mixture

Fire hazard:

The product is a flammable liquid with accompanying flammable vapor. Keep containers tightly closed. Isolate the product from heat, electrical equipment, sparks, open flame and other sources of ignition. In this case fog nozzles are preferable.

Explosion hazard:

Closed containers may rupture when exposed to extreme heat.

Reactivity:

During a fire, irritating and or toxic gases and particulate may be generated by thermal decomposition or combustion.

Advice for firefighters

Firefighting instructions:

Use water spray to keep fire exposed containers cool.

Protection during firefighting:

Wear self-contained breathing apparatus (SCBA) equipped with a full face-piece and operated in a pressure demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SBCA during clean up immediately after a fire as well as during the attack phase of the fire-fighting operations.

Additional information

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures:



Safety Data Sheet

Remove all sources of ignition (flame, hot surfaces and electrical, static or frictional sparks). Avoid contact and avoid breathing the vapors. Use self-contained breathing apparatus.

For non-emergency personnel

Protective equipment:

Wear chemical resistance (impervious) gloves

Emergency procedures:

Evacuate unnecessary personnel

For emergency responders

Protective equipment:

Equip clean-up crew with proper protection. Use appropriate personal protection equipment (PPE)

Emergency procedures:

Ventilate area

Environmental precautions

Do not flush product into public sewer, water systems or surface waters.

Methods and material for containment and cleaning up

For containment:

Stop leak if without risk. Move containers from spill area. Contain by diking with sand, earth or other non-combustible material.

Methods for cleaning up:

Wear proper personal protective clothing and equipment. Absorb spill with an inert material. Place into labeled, closed container and store into a safe location to await disposal. Change contaminated clothing and launder before reuse.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protective equipment

See Section 13 for disposal information

Section 7: Handling and storage

Precautions for safe handling

Additional hazards when processed:

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Do not breathe dust, vapor, mist or gas. Persons with a history of skin sensitization problems should not be employed in any process in which this product was used. Do not get in eyes

Hygiene measures:



Safety Data Sheet

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Conditions for safe storage, including any incompatibilities

Technical measures:

Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion proof electrical, lighting and ventilating equipment.

Storage conditions:

Keep containers tightly closed and upright when not in use. Keep from freezing. Protect from physical damage.

Incompatible products:

See section 10

Incompatible materials:

See section 10

Storage area:

The product should be stored in a cool, dry and well ventilated area, at ambient temperature directly out of the sunlight.

Special rules on packaging:

Do not store in open, unlabeled or mislabeled containers. Keep containers closed at all times when not in use.

Specific end use(s)

Coating

Section 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits:

Chemical Name	CAS #	EXPOSURE LIMITS
Toluene	108-88-3	OSHA PEL 100 ppm ACGIH TLV 20 ppm
Acetone	67-64-1	OSHA PEL 1,000 ppm ACGIH TLV 500 ppm
Methyl Ethyl Ketone	78-93-3	OSHA PEL 200 ppm ACGIH TLV 200 ppm
Isopropanol	67-63-0	OSHA PEL 400 ppm ACGIH TWA 200 ppm



Safety Data Sheet

Nitrocellulose	9004-70-0	None Established
----------------	-----------	------------------

Exposure controls

Appropriate engineering controls:

Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion proof equipment. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment:

Wear fire-proof clothing, protective goggles and gloves. Wear respiratory protection in a poor ventilated environment.

Hand protection:

Wear chemically resistant protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear fireproof clothing

Respiratory protection:

If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Thermal hazard protection:

Wear suitable protection clothing

Other information:

When using, do not eat, drink or smoke

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance:	Liquid dispersion
Color:	Clear/Transparent
Odor:	Strong aromatic solvent
Odor threshold:	Not determined
pH:	Not Applicable
Relative evaporation rate (butyl acetate=1):	Slower



Safety Data Sheet

Melting point:	Not Determined
Freezing point:	Not determined
Auto-ignition temperature:	Not available
Decomposition temperature:	Not Determined
Flammability (solid, gas):	Not Applicable
Vapor pressure:	Not Determined
Flash Point:	-4 ° F
Flash Point Method:	Tag Closed Cup
Relative vapor density @ 20 ° C:	Heavier than air
Relative density:	0.868
Density:	7.23 lbs / gal
Solubility:	Partially miscible with water
Log Pow:	Not available
Log Kow:	Not available
Viscosity, kinematic:	Not available
Viscosity, dynamic:	Not available
Explosive properties:	None, however formation of explosive air/vapor mixture is possible
Oxidizing properties:	None known
Explosive limits:	1% (V) lower & 13% (V) upper

Other information:

No further relevant information available

Section 10: Stability and reactivity

Reactivity

Exothermic reactions including polymerization may occur in contact with amines, strong acids, strong bases, alcohols, strong oxidizing agents and excessive heat.

Chemical Stability

Product is stable under normal storage conditions

Conditions to Avoid

Heat, open flames, ignition sources, and static discharge

Incompatible Materials

Avoid concentrated acids and strong oxidizers

Hazardous Decomposition Products

Thermal decomposition may produce Carbon Monoxide and Carbon Dioxide

Section 11: Toxicological information



Safety Data Sheet

Information on toxicological effects

TOXICITY MEASURES:

Chemical Name	LD50/LC50
Toluene	Oral LD50: Rat 636 mg/kg Dermal LD 50: Rabbit 8,390 mg/kg Inhalation LC 50: Rat 12.5 mg/L/4 h
Acetone	Oral LD50: Rat 5,800 mg/kg Dermal LD50: Rabbit 20,000 mg/kg Inhalation LC50: Rat 44,000 mg/m ³ /4 h
Methyl Ethyl Ketone	Oral LD50: Rat 2080 mg/kg Dermal LD50: Rabbit >3 g/kg Inhalation LD50: Rat > 2,000 ppm
Isopropanol	Oral LD50: Rat 5,045 mg/kg Dermal LD 50: Rabbit 12,870 mg/kg Inhalation LC 50: Rat 73 mg/l/4h
Nitrocellulose	Oral LD50: Rat >5,000 mg/kg Inhalation LC 50: Not available

Skin corrosion/irritation:

Caustic effect and a skin irritant

Serious eye damage/irritation:

Strong caustic effect and an irritant

Respiratory or skin sensitization:

Sensitization through prolonged inhalation is possible and skin sensitization may result from prolonged exposure. Also an irritant to the mucous membrane

Germ cell mutagenicity:

No applicable toxicity data

Carcinogenicity:

No classified

ACGIH Carcinogens:

Toluene (CAS # 108-88-3)

A3 Not classifiable as carcinogenicity to humans

Reproductive toxicity:

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Not classified

Specific target organ toxicity (single exposure):

Page 11 of 16

Revised: 03-11-2015

Supersedes: 01-03-2012



Safety Data Sheet

May cause dizziness and drowsiness

Specific target organ toxicity (repeated exposure):

May cause damage to organs (Central Nervous System) through prolonged or repeated exposure

Aspiration hazard:

May be fatal if swallowed and enters airways

Symptoms/injuries after inhalation:

The product contains organic solvents which in case of overexposure may depress the central nervous system. Abusive inhalation has been reported to be associated with birth defects in the offspring of the abusers.

Symptoms/injuries after eye contact:

Burning and stinging of the eyes may persist

Symptoms/injuries after ingestion:

Harmful if swallowed as product may enter lungs

Section 12: Ecological information

All work practices must be aimed at eliminating environmental contamination.

Toxicity

May cause long term adverse effects in the aquatic environment.

Persistence and degradability

Not determined for this product but the following information is available for its main solvent components.

TOLUENE

This compound is expected to biodegrade in aerobic and anaerobic water in 4 and 56 days respectively. It should have a half-life of 1 hour in rivers and 4 days in lakes. It should exist solely as a vapor in the atmosphere and is degraded by the reactions with photo-chemically produced hydroxyl radicals, nitrate radicals and ozone molecules. Estimated half-life with hydroxyl radicals is 3 days, nighttime reaction with nitrates half-life is 491 days and for ozone, the half-life is 27,950 days.

Bio-accumulative potential

Not determined for this product but the main solvent components of Toluene and Methyl Ethyl Ketone indicate low bio-concentration potential. No bio-accumulation expected for Acetone.



Safety Data Sheet

Mobility in soil

Not determined for this product but the following information is available for its main solvent components.

METHYL ETHYL KETONE(MEK)

Using an experimental log Kow and a regression derived equation, the Koc of MEK is estimated to be approximately 123. According to a recommended classification scheme, this estimated Koc value suggests that MEK will have a high mobility in soil.

TOLUENE

With clay minerals, Toluene adsorption is inversely proportional to the pH of the soil. The Kocs range from 37-178 in differing soils, so Toluene is expected to have high to moderate mobility in soil.

Other adverse effects

Not determined for this product

Section 13: Disposal considerations

Waste treatment methods

Regional legislation (waste):

Dispose of unused contents (incineration) in accordance with national and local regulations.

Waste disposal recommendations:

Ensure the use of properly authorized waste management companies where appropriate.

Section 14: Transport information

In accordance with ICAO/IATA/DOT/TGD

Land transport

Department of transportation (DOT):

This product is classified as Dangerous Goods, per U.S DOT regulations, under 49 CFR 172.101

UN No:	1263
Proper Shipping Name:	Paint Related Material
Hazard classes:	3
Hazard labels (DOT):	Flammable material
Packing group (DOT):	II
DOT Label(s) required:	Class 3 (Flammable)
DOT Special Provisions (49 CFR 172.102):	83
Explosive Limit and Limited Quantity Index:	5
ERAP Index:	None
Passenger Carrying Ship Index:	None



Safety Data Sheet

Passenger Carrying Road or Rail Vehicle Index: 60

Additional information

Emergency Response Guide (ERG) Number: 128

Other information:

Transport by sea

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO)

UN No.: 1263
Proper Shipping Name: Paint Related Material
Hazard Class Number: 3 (Flammable)
Labels: Class 3 (Flammable)
Packing Group: II
Special Provisions: None
Limited Quantities: 5 Liters
Excepted Quantities: E2
Packing: Instructions: P001; Provisions: PP1
IBCs: Instructions: IBC02; Provisions: None
Tanks: Instructions: T4; Provisions: T1, TP8
EmS: F-E, S-E
Stowage Category: Category B
Marine Pollutant: Not designated as a marine pollutant

Air transport

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA):

This product is classified as dangerous goods per IATA

UN Number: 1263
Proper Shipping Name: Paint Related Material
Hazard Class or Division: 3 Flammable
Hazard Label(s) Required: Class 3 (Flammable)
Packing Group: II
Excepted Quantities: E2
Passenger & Cargo Aircraft Packing Instructions: 353
Passenger & Cargo Aircraft Maximum Net Quantity per package: 5 Liters
Passenger & Cargo Aircraft Limited Quantity Packing Instructions: Y341
Passenger & Cargo Aircraft Limited Quantity Maximum Net Quantity per package: 1 Liter
Cargo Aircraft Only Packing Instructions: 364
Cargo Aircraft Only Maximum Net Quantity per Package: 60 Liters



Safety Data Sheet

Special Provisions:

A3

ERG Code:

3L

Section 15: Regulatory information

U.S. Federal Regulations

U.S. OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations

U.S SARA Reporting Requirements:

The following components of this product are subject to reporting requirements of sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.

CHEMICAL	SECTION 302 EHS (TPQ) (40 CFR 355, Appendix A)	SECTION 304 RQ (40 CFR Table 302.4)	SECTION 313 TRI (40 CFR 372.65)
Toluene	No	No	Yes
Acetone	No	No	No
Methyl Ethyl Ketone	No	No	Yes

SARA Section 311/312 (40 CFR 370) Hazard Categories:

ACUTE: Yes; CHRONIC: Yes; FIRE: Yes; REACTIVE: No; SUDDEN RELEASE: No

Toxic Substances Control Act (TSCA):

All components of this product are included on the TSCA inventory

U.S. CERCLA Reportable Quantity (RQ):

Toluene= 1000 lb (454 kg); Methyl Ethyl Ketone 5000 lb (2270 kg); Acetone 5,000 lb (2270 kg);

U.S. Clean Air Act Threshold Quantity (TQ):

The Toluene, Methyl Ethyl Ketone and components are listed as Hazardous Air Pollutants (HAPs) generally known or suspected to cause serious health problems. These chemicals are included on this list.

U.S. Clean Water Act Requirements:

Ethyl Benzene, Toluene and Xylene are designated as hazardous substances under Section 311 (b) (2) (A) of the Federal Water Pollution Control Act and further regulated by the Clean Water Act Amendments. The listed products are subjected to effluent limitations.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):

The Toluene component is on the California Proposition 65 lists. WARNING: This product contains a chemical known to the State of California to cause cancer or developmental harm.

Canadian WHMIS Classification:

This product is classified as a controlled product. Hazard classes B2 (Flammable liquid); D2B Toxic



Safety Data Sheet

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists:

Under Section 64, Xylene and Toluene are not considered toxic but are listed on the Priority Substances List 1.

European Inventory of Existing Chemicals (EINECS):

All of the components of this product are included on EINECS.

Section 16: Other information

Indication of changes:

Other information:

Full text of H phrases:

STOT SE 3	Specific Target Organ Toxicity-Single Exposure, Category 3, Narcosis
STOT RE 2	Specific Target Organ Toxicity-Repeated Exposure, Category 2



NFPA health hazard: 2-Moderately toxic or hazardous material which require additional PPE or equipment than safety goggles and gloves.

NFPA fire hazard: 3-Liquids and solids that can be ignited under almost all ambient conditions

NFPA reactivity: 0-Normally stable, even under fire exposure conditions, and not reactive with water

Notice to Reader

The information provided herein is believed to be accurate at the time of preparation or prepared from sources deemed to be reliable, but it is the full responsibility of the user to investigate and comprehend other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. **Kel-Glo Corp. makes no warranty, expressed or implied, concerning the product or merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided by Kel-Glo Corp.,** except that the product shall conform to Kel-Glo's specification.